

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 October 2003 (09.10.2003)

PCT

(10) International Publication Number
WO 03/082479 A1

(51) International Patent Classification⁷: **B05C 17/02**,
17/025, 17/035

(21) International Application Number: PCT/SG03/00015

(22) International Filing Date: 24 January 2003 (24.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
200201815-8 1 April 2002 (01.04.2002) SG

(71) Applicant and

(72) Inventor: **ER, Poh, Leong** [SG/SG]; Blk 2, No. 449 Lor
3, Geylang, Singapore 388920 (SG).

(74) Agent: **LAWRENCE Y D HO & ASSOCIATES PTE LTD.**; 30 Bideford Road, #07-01 Thongsia Building, Singapore 229922 (SG).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A PAINT ROLLER FOR SELECTIVELY APPLYING PAINT AT SURFACE CORNERS



(57) Abstract: A paint roller (10) has a frustoconically-shaped applicator (12), a paint-absorbable member (14) and a movement coupler (16). The applicator (12) has a coupling portion (18) and two opposite ends (20, 22) and is rotatable at the coupling portion (18) about a rotary axis (24). The end (20) is a coupling end (20) that has a planar cross-section smaller than that of the other end (22). The coupling portion (18) is formed at the coupling end (20) and is disposed centrally thereof. The movement coupler (16) has a rotary connecting portion (40) that is detachably coupled to the applicator (12) at the coupling portion (18) for rotary movement about the rotary axis (24) and a pivotal connecting portion (42) that is adapted to coact with a pivot mount of a handle (not shown) for pivotal movement of the applicator (12).

A PAINT ROLLER FOR SELECTIVELY APPLYING PAINT AT SURFACE CORNERS

Field of the Invention

5 The present invention relates to apparatus for applying fluids such as, for example, paint onto surfaces. In particular, the present invention relates to a paint roller for selectively applying paint at surface corners.

Background of the Invention

10 Paint rollers for applying paint onto surfaces are known. Typically, such paint rollers have paint-absorbing surfaces that are dipped into paint containers and then rolled over surfaces that are to be painted. Another type of paint rollers has a permeable surface through which paint, stored inside such paint rollers, can flow through for application onto surfaces that are to be painted.

15 Generally, existing paint rollers works well for a flat surface on which only a single paint shade or color is to be applied. However, a problem arises when such paint rollers are used to apply paint at surface corners formed, for example, by two walls or between a wall and a ceiling. This is a problem because paint desired on one
20 surface may be undesirably applied onto an adjacent surface.

 Prior art paint rollers that alleviate the above problem include US Patent 5,623,740, issued to Burns et al., in which an apparatus provides a guard shield that acts as a barrier to paint being applied onto an adjacent surface. Such prior art paint
25 rollers provide shield-like barriers or guards that are detachably mounted to the paint rollers. However, use of the shield-like barriers or guards causes other problems. For example, a guard may be required to contact an adjacent surface for alignment purposes as well and this is a problem when an adjacent surface has wet paint or is delicate. Consequently, the adjacent surface can be damaged by abrasion with the

guard. Furthermore, shield-like barriers or guards are accessories that typically require assembling or attaching, which adds complexity to prior art paint rollers.

Therefore, a need clearly exists for a novel paint roller for selectively
5 applying paint at surface corners and that does not need separate accessories such as a barrier or a guard to be assembled or attached.

Brief Summary of the Invention

The present invention seeks to provide a paint roller for selectively applying
10 paint at surface corners.

Accordingly, in one aspect, the present invention provides a paint roller comprising:

15 a frustoconically-shaped applicator having two opposite ends, a coupling portion disposed at one of the opposite ends, and an external surface between the two opposite ends, the frustoconically-shaped applicator being rotatable at the coupling portion about a rotary axis;
and
at least one paint-absorbable member mounted to the external
20 surface.

In another aspect, the present invention provides a paint roller comprising:

25 a frustoconically-shaped applicator having two opposite ends, a coupling portion disposed at one of the opposite ends, and an external surface between the two opposite ends, the frustoconically-shaped applicator being rotatable at the coupling portion about a rotary axis;
at least one paint-absorbable member mounted to the external surface;
a handle having a pivot mount;
30 and

a movement coupler detachably coupled to the coupling portion
and to the pivot mount.

Brief Description of the Drawings

5 A preferred embodiment and alternate embodiments of the present invention
are described, by way of example, with reference to the drawings of which:

FIG. 1 is a perspective view of a paint roller comprising a frustoconically-
shaped applicator and a movement coupler in accordance with the preferred
10 embodiment;

FIG. 2 is a side view of the paint roller of FIG. 1;

FIG. 3 is an end view of the paint roller of FIG. 1 looking at one opposite end
15 of the frustoconically-shaped applicator;

FIG. 4 is an end view of the paint roller of FIG. 1 looking at the other
opposite end of the frustoconically-shaped applicator;

20 FIG. 5 is a perspective view of the paint roller of FIG. 1 with the movement
coupler separated and a part of a handle for the paint roller;

FIG. 6 is a perspective view of a paint roller in accordance with an alternate
embodiment of the present invention;

25

and

FIG. 7 is a side view of a frustoconically-shaped applicator for the paint roller
of FIG. 6.

30

Detailed Description of the Drawings

A paint roller in accordance with a preferred embodiment and an alternate embodiment of the invention are described. In the following description, details are provided to describe these embodiments. However, it shall be apparent to one skilled
5 in the art that the invention may be practiced without such details. Some of these details may not be described at length so as not to obscure the invention.

There are many advantages of the embodiments of the invention. One advantage of the embodiments is that contact with an adjacent surface by a paint-
10 absorbable member of the paint roller is avoided, or at least alleviated, when using the paint roller to paint a surface.

Another advantage of the embodiments of the invention is that the paint roller is simple to use and does not require an accessory such as a barrier or a guard.
15 Without such an accessory, the likelihood of contact with an adjacent surface having wet paint or damage to the adjacent surface is avoided or reduced.

A further advantage of the invention is that the paint roller can receive paint directly onto a paint-absorbable member from an external paint container in the
20 preferred embodiment. In an alternate embodiment, the paint roller has a chamber that stores paint and that is coupled to the paint-absorbable member via at least one paint-permeable portion.

Referring now to FIG. 1, a perspective view of a paint roller 10 in accordance
25 with the preferred embodiment of the invention is illustrated. The paint roller 10 comprises a frustoconically-shaped applicator 12, a paint-absorbable member 14 and a movement coupler 16.

The frustoconically-shaped applicator 12 has a coupling portion 18 and two
30 opposite ends 20, 22 and is rotatable at the coupling portion 18 about a rotary axis 24. The opposite end 20 is a coupling end 20 that has a planar cross-section smaller than

a corresponding planar cross-section of the other opposite end 22. The coupling portion 18 is formed at the coupling end 20 and is disposed centrally relative to the planar cross-section of the coupling end 20.

5 The paint-absorbable member 14 is mounted to an external surface 30 of the frustoconically-shaped applicator 12 between the two opposite ends 20,22. The external surface 30 is indicated in a side view of the paint roller 10 shown in FIG. 2. The paint-absorbable member 14 can be formed with foam or sponge-like material.

10 The movement coupler 16 is detachably coupled to the frustoconically-shaped applicator 12 at the coupling portion 18. The movement coupler 16 comprises a rotary connecting portion 40 and a pivotal connecting portion 42. The rotary connecting portion 40 is adapted to coact with the coupling portion 18 for rotary movement of the frustoconically-shaped applicator 12 about the rotary axis 24. The
15 pivotal connecting portion 42 is adapted to coact with a pivot mount of a handle (not shown) for pivotal movement of the frustoconically-shaped applicator 12.

FIG. 3 is an end view of the paint roller 10 looking at the opposite end 22 and FIG. 4 is an end view of the paint roller 10 looking at the other opposite or coupling
20 end 20. In these end views, disposition of the paint-absorbable member 14, the external surface 30 and the movement coupler 16 relative to each other are illustrated. In addition, these end views illustrate the planar cross-section of the two opposite ends 20,22.

25 Referring now to FIG. 5, a perspective view of the paint roller 10 with the movement coupler 16 separated and a part of handle 50 for the paint roller 10 is illustrated. The handle 50 has a pivot mount 52 that couples to the pivotal connecting portion 42 of the movement coupler 16. Apertures 54,56 are provided, respectively,
30 at the pivotal connecting portion 42 and the pivot mount 52 to enable a pivot coupling thereat. With the apertures 54a,54b and a pin (not shown), the pivotal connecting portion 42 is adapted to coact with the pivot mount 52 for pivotal

movement of the frustoconically-shaped applicator 12. The coupling portion 18 has a knob 58 that couples to an aperture 60 of the rotary connecting portion 40 of the movement coupler 16.

5 A perspective view of a paint roller 70 in accordance with an alternate embodiment of the present invention is illustrated in FIG. 6. Other than elements similar to the paint roller 10, the paint roller 70 further comprises a chamber 72 for storing paint, a closable inlet 74 that leads into the chamber 72 and an abutment member 76. The abutment member 76 is mounted to the opposite end 22 and serves
10 to alleviate contact of the paint-absorbable member 14 with adjacent surfaces that are not being painted.

Referring to FIG. 7, a side view of a frustoconically-shaped applicator 78 for the paint roller 70 is illustrated. The frustoconically-shaped applicator 78 comprises
15 at least one paint-permeable portion 80. In this alternate embodiment, the at least one paint-permeable portion 80 comprises slits 82 through which paint is provided to the paint-absorbable member 14 from the chamber 72. The closable inlet 74 is disposed at the opposite end 22 and has a cover 84. Paint is poured into the chamber 72 via the closable inlet 74 and the chamber 72 is then capped using the cover 84.

20

While the present invention has been described in detail for the above embodiments with reference to FIGs. 1 to 7, it should be understood that FIGs. 1 to 7 are illustrative of the embodiments without limiting the invention. For example, the paint-permeable portion 80 has the slits 82 oriented as shown in FIG. 7. However,
25 other shapes and different orientation of such shapes may be provided at the paint-permeable portion 80. Also, the closable inlet 74 may be placed at other locations that do not restrict or limit movement of the frustoconically-shaped applicator 78. Furthermore, coupling between the coupling portion 18 and the movement coupler 16 may also be provided in another manner although not shown in the embodiments
30 as described and illustrated. Accordingly, persons skilled in the art can make various

modifications and improvements without departing from the spirit and the scope of the present invention.

Claims

What is claimed is:

1. A paint roller comprising:

5 a frustoconically-shaped applicator having two opposite ends, a coupling portion disposed at one of said opposite ends, and an external surface between said two opposite ends, said frustoconically-shaped applicator being rotatable at said coupling portion about a rotary axis;

and

10 at least one paint-absorbable member mounted to said external surface.

2. The paint roller as claimed in Claim 1, and further comprising a movement coupler detachably coupled to said coupling portion.

3. The paint roller as claimed in Claim 2, wherein said movement coupler comprises a rotary connecting portion adapted to coact with said coupling portion for rotary movement about said rotary axis.

20 4. The paint roller as claimed in Claim 2, wherein said movement coupler comprises a pivotal connecting portion adapted to coact with a pivot mount of a handle for pivotal movement of said frustoconically-shaped applicator.

25 5. The paint roller as claimed in Claim 1, wherein said frustoconically-shaped applicator comprises a chamber for storing paint.

30 6. The paint roller as claimed in Claim 5, wherein said frustoconically-shaped applicator further comprises at least one closable inlet leading into said chamber.

7. The paint roller as claimed in Claim 6, wherein said at least one closable inlet is disposed at one of said opposite ends.
- 5 8. The paint roller as claimed in Claim 5, wherein said chamber comprises at least one paint-permeable portion coupled to said at least one paint-absorbable member.
- 10 9. The paint roller as claimed in Claim 1, wherein one of said opposite ends is a coupling end, said coupling portion being formed at said coupling end.
- 15 10. The paint roller as claimed in Claim 9, wherein said coupling end has a planar cross-section smaller than a corresponding planar cross-section of the other opposite end.
- 20 11. The paint roller as claimed in Claim 10, wherein said coupling portion is disposed centrally relative to said planar cross-section of said coupling end.
12. The paint roller as claimed in Claim 1, and further comprising at least one abutment member mountable to one of said opposite ends.

13. A paint roller comprising:

a frustoconically-shaped applicator having two opposite ends, a coupling portion disposed at one of said opposite ends, and an external surface between said two opposite ends, said frustoconically-shaped applicator being rotatable at said coupling portion about a rotary axis;

at least one paint-absorbable member mounted to said external surface;

a handle having a pivot mount;

and

a movement coupler detachably coupled to said coupling portion and to said pivot mount.

14. The paint roller as claimed in Claim 13, wherein said movement coupler comprises a rotary connecting portion adapted to coact with said coupling portion for rotary movement of said frustoconically-shaped applicator about said rotary axis.

15. The paint roller as claimed in Claim 13, wherein said movement coupler comprises a pivotal connecting portion adapted to coact with said pivot mount for pivotal movement of said frustoconically-shaped applicator.



16. The paint roller as claimed in Claim 13, wherein said frustoconically-shaped applicator comprises a chamber for storing paint.

17. The paint roller as claimed in Claim 16, wherein said frustoconically-shaped applicator further comprises at least one closable inlet leading into said chamber.

18. The paint roller as claimed in Claim 17, wherein said at least one closable inlet is disposed at one of said opposite ends.

19. The paint roller as claimed in Claim 16, wherein said chamber comprises at least one paint-permeable portion coupled to said at least one paint-absorbable member.
- 5
20. The paint roller as claimed in Claim 13, wherein one of said opposite ends is a coupling end, said coupling portion being formed at said coupling end.
- 10
21. The paint roller as claimed in Claim 20, wherein said coupling end has a planar cross-section smaller than a corresponding planar cross-section of the other opposite end.
- 15
22. The paint roller as claimed in Claim 21, wherein said coupling portion is disposed centrally relative to said planar cross-section of said coupling end.
- 20
23. The paint roller as claimed in Claim 13, and further comprising at least one abutment member mountable to one of said opposite ends.

- 1/4 -



- 2/4 -




FIG. 3





FIG. 4

- 3/4 -

*FIG. 5*

- 4/4 -




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SG03/00015

A. CLASSIFICATION OF SUBJECT MATTERInt. Cl. ⁷: B05C 17/02, 17/025, 17/035

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DWPI: B05C 17/02, 17/025, 17/035 and keywords: frust+, conical+, taper+, corner+, coupl+

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X P,Y	AU 200221312 A1 (PASQUALE P Z) 6 March 2002 See pages 2 and 3, figures 1 and 8 See pages 2 and 3, figures 1 and 8	1, 5, 8-12 6-7
X Y	CA 2101124 A1 (BAZYDLO S) 23 January 1995 See whole document See whole document	1, 9-12 5-8
X Y	US 5412832 (IRVEN) 9 May 1995 See column 2 See column 2	1, 9-12 5-8

☒ Further documents are listed in the continuation of Box C☒ See patent family annex

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
25 February 2003Date of mailing of the international search report
14 MAR 2003

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE
PO BOX 200, WODEN ACT 2606, AUSTRALIA
E-mail address: pct@ipaustralia.gov.au
Facsimile No. (02) 6285 3929

Authorized officer

THARU FERNANDO

Telephone No : (02) 6283 2486

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SG03/00015

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Derwent Abstract Accession No. 84-286393/46 Class P42 & NL 8301130 A (SCHULER J P) 16 October 1984 See abstract and figure 1	1
Y	GB 2143158 A (MULTIGOOD BV) 6 February 1985 See whole document	6-7

Information on patent family members

PCT/SG03/00015

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
AU	21312/02	AU	200221312	AU	20013562		
NL	8301130/83	NONE					
CA	2101124	NONE					
US	5412832	CA	2146383				
GB	2143158	DE	3425995	GB	2179569	JP	60097069
		NL	8402073	US	4555195	ZA	8404991
END OF ANNEX							